

TUBO DE FIBRA
TUBING CONNECTOR
TUBO IN FIBRA DI VETRO
TUYAU EN FIBRE DE VERRE

Tubo de fibra para empalme de mangueras en sistemas de escape húmedos. Bajo demanda, puede suministrarse hasta 457 mm.

Manufactured in fiberglass. Available on demand up to 18".

Tubo in fibra di vetro. Disponibile sotto richiesta fino a 457mm.

Tuyau en fibre de verre. Disponible sur demande jusqu'à 457mm.

REF	Ø EXT (mm)		
TRI260-4001	102	121°C	152 mm
TRI260-4121	115		
TRI260-5001	127		
TRI260-6001	152		


MANGUERA ESCAPE
EXHAUST HOSE
TUBO DI SCARICO
TUYAU D'ÉCHAPPEMENT

Manguera de goma de espiral ondulada para sistemas de escape y refrigeración. Su particular estructura permite efectuar radio de curvatura de 1 a 1,5 vueltas por el diámetro interno.

General purpose hose. Hardwall corrugated cover rubber hose. Extremely flexible. The construction ensures bending radius up to 1 / 1.5 for the inside diameter.

Tubo in gomma spiralato ondulato per il sistema di scarico e raffreddamento. La sua particolare struttura consente di effettuare un raggio di curvatura da 1 a 1,5 giri per il diametro interno.

Tuyau d'échappement et de refroidissement en caoutchouc ondulé en spirale. Sa structure particulière lui garantit un rayon de courbure jusqu'à 1 / 1,5 de son diamètre intérieur.

SCAMO / SP

REF	Ø (mm)			
GS35033	30	30 mm	-30°C → 100°C	x m
GS35034	40	40 mm		
GS35045	45	45 mm		
GS35035	51	51 mm		
GS35036	60	60 mm		
GS35037	63,5	63,5 mm		
GS35038	76	76 mm		
GS35039	80	80 mm		
GS35040	90	90 mm		
GS35041	102	152 mm		
GS35042	120	240 mm		
GS35043	127	255 mm		
GS35044	152	305 mm		
GS35046	203	815 mm		
GS35047	254	1.270 mm		



Rina CE 0474
Lloyd's Register 96/00/127

ISO 13363 - 2004 T-2 Class B
SAE J 2006 - 2003 R2



ht
hoses technology

MANGUERA CARBURANTE
FUEL HOSE
TUBO DI CARBURANTE
TUYAU DU CARBURANT

Tubo de goma para el transporte de carburante (diesel o gasolina). Construida en goma negra (NBR). Contenido aromático no superior al 60%. Resistente a la abrasión de los agentes marinos.

Long length rubber hose, suitable for loading diesel, bio-diesel and unloaded fuel for marine pleasure craft inboard engines up to 24 m.

Tubo in gomma per il passaggio di carburante (diesel o benzina). In gomma nera (NBR). Per motori entrobordo su imbarcazioni da diporto fino a 24m.

Tuyau en caoutchouc pour le passage du carburant (diesel ou essence). Caoutchouc noir (NBR). Pour moteurs in-bord sur bateaux de plaisance jusqu'à 24m.

CARBO/7840/A1

REF	Ø (mm)				
GS35049	6x16	14 bar	35 mm	-30°C → 100°C	40 m
GS35050	8x17	14 bar	50 mm		40 m
GS35051	10x19	14 bar	60 mm		40 m
GS35052	12x22	10 bar	75 mm		20 m
GS35053	16x26	10 bar	100 mm		40 m
GS35054	19x30	10 bar	115 mm		20 m
GS35055	25x37	10 bar	250 mm		x m
GS35056	30x42	10 bar	300 mm		x m
GS35057	32x44	10 bar	320 mm		x m
GS35058	35x47	10 bar	350 mm		x m
GS35059	38x52	10 bar	380 mm		x m
GS35060	40x54	10 bar	400 mm		x m
GS35061	45x59	10 bar	450 mm		x m
GS35062	51x65	10 bar	500 mm		x m
GS35063	60x74	10 bar	600 mm		x m



Rina CE 0474
Lloyd's Register 96/00/127

SAE J 1527 - 2004
USCG A1 R1
ISO 7840 A-1 2004 CE

ht
hoses technology

De goma para diesel y gasolina sin plomo. Ideal para fueraborda. Refuerzos textiles internos. Muy flexible. Contenido aromático 50%.

Rubber Hose suitable for loading mineral oils, diesel and unloaded fuel

In gomma per diesel e benzina senza piombo. Ideale per motori fuoribordo. Tessuto interno rinforzato. Molto flessibile.

En caoutchouc pour diesel et essence sans plomb. Idéal pour les moteurs hors-bord. Tissu intérieur renforcé. Très flexible

CARBUPOMP/10NL

REF	Ø (mm)				
GS35031	6x12	10 bar	50 mm	-25°C → 80°C	50 m
GS35032	8x15	10 bar	65 mm		50 m



ISO R1307

ht
hoses technology

