

Lights for topsides, gangplanks and below the waterline

Pair of LED docking lights

IP65

LED

2-mode docking lights: 20°-angle, 320 mA HD LED bow light + 85°-angle 80 mA side light. The lights are wired separately. Recessless mounting. Polished AISI 316 SS body.

Code	Description	V	Lumen	K	LED beam angle	LED	↔ mm
13.653.00	Docking lights	12	280/125	6000	20° + 85°	320+80 mA	90.8x66.2x20




ATTWOOD bow LED light

LED

Polished stainless steel body. Totally watertight. 120° light beam. High-power LED equivalent to 50W halogen bulb. **No recess needed**. Sold in pairs.

Code	V	W	Lumen	LED beam angle	↔ mm
13.652.01	12	5 each	750	120°	114x71x30




Compact fairing light pair with LED bulb

AISI 316

Made of mirror-polished AISI 316 stainless steel. Front protection lens.

Code	LED included	Cone	Spare LED
13.254.13	12 V 4 W	45° FMW	14.258.56
13.254.14	24 V 3.5 W	45° FMW	14.258.59



OSCULATI




Fairing light pair, built-in model fitted with Sealed Beam 4" watertight bulb.

AISI 316

Made of mirror polished AISI 316 stainless steel.

Code	Bulb included	Cone	Spare bulb
13.258.12	12 V - 50 W x 2	70°x30°	14.249.11
13.258.24	24 V - 50 W x 2	40°x5°	14.249.08



OSCULATI

